



Basis specification

- **Chassis:**
 - › Type: MB Atego 1330F 4x2 Euro 6
 - › Engine output: 220 kW (300 hp)
 - › Transmission: automatic PowerShift transmission G140-8
 - › Wheelbase: 3.860 mm
 - › Rosenbauer underride protection
 - › One-piece electrical driven aluminium roller shutters incl. closure of lower equipment compartment
 - › Accessible lower equipment compartments with rotating shelves, horizontally and vertically adjustable fixtures
- **Cabin:**
 - › Double cab integrated into the body (IDC) with a reach-through to the front into the drivers cab
 - › Crew: 1/8 (2+3+4)
 - › 2x COMFORT SCBA brackets against and 2x in direction of travel
 - › 3-point safety belts with removeable shoulder strap for SCBA seats
 - › Crew cab doors with glass
 - › Pneumatic hinged steps below crew cab doors
 - › Illuminated handle bars, ambient lighting in the crew cab, base lighting on bench box
- **Control system:**
 - › LCS (Logic Control System), based on CAN-Bus technology.
 - › Controlling and monitoring of chassis, body, fire fighting systems and alarm units.
 - › Intuitive operating via 10" display in drivers cab and pump compartment (GR7).
- **Vehicle body:**
 - › Self-supporting Rosenbauer large-capacity body frame in light weight construction, made of aluminium laser parts, aluminium extrusion profiles and aluminium sandwich panels
 - › Subframe integrated into sandwich base. Especially low loading and unloading heights
 - **Extinguishing system:**
 - › Low pressure pump N35 in light alloy with LCS display controlling with design cover
 - › Pump pressure regulator
 - › Free water tank inlet (2 pipes) with damped flap
 - › Central water inlet, electro-pneumatic, NW 80 for tank and pump
 - › Water tank content: 2.000 liter with automatic level regulation
 - › Foam tank: 120 liter
 - › Direct injection foam proportioning system VARIOMATIC with 2 injection points

CT Frame - Compact Technology

HLF 10



- **Outlets:**
 - › 4x LP outlets with screw-down valves (2 with foam)
 - › Laterally exposed
- **Rapid intervention device:**
 - › 1x LP hose reel with RB100 C nozzle
- **Alarm units:**
 - › Rosenbauer cab roof superstructure with integrated LED flashing lights
 - › LED flashing lights integrated in the rear of the body
 - › Flashing blue LED stripe integrated into the roof gallery over the length of the vehicle body
 - › 2 additional LED flashing lights on the radiator grille
 - › Compressor horn with 4 bells
 - › Traffic guidance system with 6 LED flashing lights
- **Lighting:**
 - › Near and distance ambient lighting with high performance LED stripes integrated into the roof gallery over the length of the vehicle body
 - › Lighting tower 6x40W LED 3,2 m pneumatic
- **Additional features:**
 - › Remote start function for RB generator
 - › Built-in generator 8kW EPS XS 400VAC
 - › Rear view camera with image display in the drivers cab
- **Brackets and body components:**
 - › Brackets for standard loading HLF 10 according to DIN 14530-26
 - › Brackets for substantial additional loading
 - › Hygiene board COMFORT with compressed air pistol
 - › Roof box COMFORT with integrated LED lighting
 - › Ladder mounting incl. payroll COMFORT



Dimensions and weight:

L x W x H	~ 7.000 x 2.350 x 3.100 mm
Permissible total weight	13.500 kg

Sales information:

Product code	PM321
Model range	CT Frame

Contact

Rosenbauer International AG
 Paschinger Straße 90
 4060 Leonding, Austria
 Tel.: +43 732 6794 - 0
 Fax: +43 732 6794 -91

www.rosenbauer.com

Follow us on

Text and images non-binding. The images may depict special editions that are only available at an additional charge. Subject to change due to technical advances.