



Basis specification

▪ Chassis:

- › Type: MB Sprinter 519 CDI 4x4 Euro 6
- › Engine output: 140 kW (190 hp)
- › Transmission: 6-gear manual transmission ECO Gear 480
- › Wheelbase: 3.665 mm

▪ Cabin:

- › Double cab integrated into the body (IDC) with reach-through to the front
- › Crew: 1/7 (2+3+3)
- › 3x COMFORT SCBA brackets in direction of travel
- › 3-point safety belt with removeable shoulder strap for SCBA seats
- › Rigid steps for crew cab incl. storage compartment behind it
- › Crew cab doors with glass
- › Central locking and electr. window regulator for crew cab doors
- › Illuminated handle bars, ambient lighting in crew cab, base lighting on bench box

▪ Vehicle body:

- › Self-supporting Rosenbauer large-capacity body frame in light weight construction made of aluminium laser parts, aluminium extrusion profiles and aluminium sandwich panels
- › Subframe integrated in sandwich base Especially low loading and unloading heights
- › One-piece roller shutters with continuous bar lock (lockable)
- › Aluminium rear flap with bar lock handle bar in the rear

▪ Control system:

- › LCS (Logic Control System), based on CAN-Bus technology.
- › Controlling and monitoring of chassis, body and alarm units.
- › Intuitive operating via 10" display in drivers cab with automatic day/night switch

CT Frame - Compact Technology

KLF-A



Alarm units:

- › Rosenbauer cab roof superstructure with integrated LED flashing lights
- › LED flashing lights integrated in the rear of the body
- › Flashing blue LED stripe integrated into the roof gallery over the length of the vehicle body
- › 2 additional LED flashing lights on the radiator grille
- › acoustic alarm unit with e-horn

Lighting:


- › Near and distance ambient lighting with high performance LED stripes integrated into the roof gallery over
 - (a) the length of the vehicle body
 - (b) the width of the vehicle body

Additional features:

- › Shutter rear view camera incl. microphone in the rear, image display in the front
- › Traffic guidance system with 6 orange LED flashing lights

Brackets and body components:

- › Brackets for loading KLF
- › TS full-load pull-out COMFORT for FOX 4
- › Generator RS14 on rotating platform COMFORT
- › Well-arranged pull-out drawer COMFORT for bar tools
- › Ladder mounting COMFORT for plug-in ladder



Dimensions and weight:

L x W x H	~ 6.250 x 2.100 x 2.700 mm
Permissible total weight	5.500 kg

Sales information:

Product code	PM321
Model range	CT Frame

Contact

Rosenbauer International AG
 Paschinger Straße 90
 4060 Leonding, Austria
 Tel.: +43 732 6794 - 0
 Fax: +43 732 6794 -91

www.rosenbauer.com

Follow us on

Text and images non-binding. The images may depict special editions that are only available at an additional charge. Subject to change due to technical advances.