

# CT Profile - Compact Technology

## Portable Pump Vehicle - Water



TSF-W acc. to DIN 14530-17 / Country Procurement MVP

Deutsch



### Basis specification

#### Chassis:

- › Type: IVECO Daily 72C18 4x2
- › Engine power: 132 KW (180 hp)
- › Transmission: 8 Gear Converter Automatic HI-MATIC
- › Wheel base: 3,750 mm
- › Color: red RAL 3000

#### ▪ Crew Cab:

- › Crew: 1/5 (2+4+0)
- › Rosenbauer Crew Cab with 4x SCBA brackets against driving direction
- › 3-point safety belts for all seats
- › Crew cab doors with electric power windows and central locking
- › Parking heater in the crew cab

#### ▪ Vehicle body:

- › Rosenbauer aluminum profile superstructure of self-supporting bolted and bonded aluminum sheet and profile construction with aluminum sandwich panels
- › Manual roller shutters with continuous barlock closure at the sides and in the rear
- › Generous rear step can be folded down

#### ▪ Compartments:

- › COMFORT fixing device program and equipment carrier for optimized removal and safe storage of equipment
- › COMFORT inclined pull-out for portable pump

#### ▪ Equipment:

- › Acc. to DIN 14530-17
- › Brackets incl. drain roller for plug-in ladders

#### ▪ Control system:

- › Clearly arranged switch panel on the dashboard for operating the following functions (rotating beacons, acoustic signal system, front strobe lights, ambient lighting, etc.)

#### ▪ Extinguishing system:

- › Portable Pump FOX 4 (PFPN 10/1500 acc. to DIN EN 1028)
- › Polypropylen Watertank: 1,000 liters acc. to DVGW W405-B1 (A) F category 4
- › Water level indicator in the driver's cab and in the pump dashboard

#### ▪ Outlets:

- › LP outlet Storz C on the right for rapid intervention
- › Folding hose (2x C42) incl. hollow jet pipe stored in removable tray

#### ▪ Tank filling line:

- › Storz B pressure inlet with manual ball valve on the right

# CT Profile - Compact Technology

## Portable Pump Vehicle - Water



### ▪ Lightmast:

- › Pneumatic lightmast with 4x LED headlights incl. electric turning and swiveling unit (approx. 2,400 mm extension height)

### ▪ Optical and acoustic warning devices:

- › 2x LED flashing lights on the cab roof
- › 2x LED flashers integrated in the front body
- › 2x LED flashers integrated in the rear body
- › 2x LED flashers on the radiator grille
- › Acoustic signal system (electronic horn) with bar microphone for voice announcements

### ▪ Additional equipment:

- › Ambient lighting with powerful, continuous LED strips on the left, right and in the rear
- › Helmet holders in the driver's cab and crew compartment for each seat
- › 230V power supply including start interruption and LED charging indicator light
- › Extendable hygiene board with water connection



### Dimensions and weight:

|                          |                              |
|--------------------------|------------------------------|
| L x W x H                | ca. 6,300 x 2,320 x 2,900 mm |
| Permissible total weight | 7,200 kg                     |

### Sales information:

|              |                     |
|--------------|---------------------|
| Product code | PM511               |
| Model range  | CT Profile (hybrid) |

### Contact

Rosenbauer International AG  
 Paschinger Street 90  
 4060 Leonding, Austria  
 Tel.: +43 732 6794 - 0  
 Fax: +43 732 6794 -91

[www.rosenbauer.com](http://www.rosenbauer.com)

Follow us on

Text and images non-binding. The images may depict special editions that are only available at an additional charge. Subject to change due to technical advances.